



Remark:
 1.MATERIAL:
 1.1 Housing:thermoplastic plastics.
 1.2 terminals:Copper Alloy
 1.3 Front Shell:Copper Alloy/SPCC.
 Middle Shell:SPCC
 2.characteristics:
 2.1 Rating Voltage : 30V AC.
 2.2 Rating Current:PIN1&PIN4(Vbus&Correponding ground PIN)
 1.8A MAX Other PINS 0.25A min.
 2.3 Contact Resistance:PIN1&PIN4:30 mΩ MAX. Other PINS: 50 mΩ
 2.4 Insulation Resistance:100 MΩ MIN.
 2.5 Withstanding Voltage:AC 100V between adjacent contacts
 2.6 Mating force: 3.57Kgf MAX(35N MAX)
 2.7 Extraction force:1Kgf Min(9.8N Min)
 2.8 Life test:1500Cycles MIN.
 2.9 Temperature Range: -30℃~+80℃.

U321-052B-127018

B: 不锈钢镀镍
 1: 吸塑
 7: 蓝色盒
 1: 1u" Au
 2: PA66

TOLERANCE UNLESS OTHERWISE SPECIFIED		FLW 深圳市华联威电子科技有限公司 HUA LIAN WEI TECHNOLOGY ELECTRONICS CO.;LTD.						
.XXX ±0.10	.X* ±3°	APPROVED	PART NAME:	USB 3.0 AF 双层X4				
.XX ±0.20	.XX* ±2°	CHECKED	PART No:	U321-052B-127018	C		A	
.X ±0.30		DRAWN	weihong	PROJECTION:	UNIT:	SCALE	SHEET	REV.
		DATE	2021.6.19		mm	1:1	10F1	A0