



- NOTES:
- MATERIAL:
 - Housing:thermoplastic plastics
 - terminals:Copper Alloy
Gold plated in contact area:
Tin plated in termination
Nickel Plated overall
 - Shell:Steel&Copper Alloy
Nickel Plated overall
 - ELECTRICAL CHARACTERISTICS:
 - Rating Current :1.5 Ampere
 - Rating Voltage :30 V Max
 - Contact Resistance:30 Milli ohms
 - Insulation Resistance:1000 Mega ohms Min.
 - MECHANICAL CHARACTERISTICS:
 - Connector Mating force: 35N MAX(3.57Kgf)
 - Connector Unmating force:10N min(1.02Kgf)
 - Durability:1500Cycles.
 - ENVIRONMENT CHARACTERISTICS:
 - Operating temperature:-0°C to +50°C
 - Storage temperature:-20°C to +60°C

- | | | | | |
|---|------------|---|--------------|------|
| 1 | USB 双孔A公铁壳 | 1 | 铁, T=0.3MM | 镀镍 |
| 2 | USB 双孔A公端子 | 4 | 黄铜, T=0.25MM | 前金后锡 |
| 3 | USB 双孔A公胶芯 | 1 | 白PBT塑料 | |

TOLERANCE UNLESS OTHERWISE SPECIFIED		FLW 深圳市华联威电子科技有限公司				
.XXX ±0.10	.X' ±3'	HUA LIAN WEI TECHNOLOGY ELECTRONICS CO.;LTD.				
.XX ±0.20	.XX' ±2'	APPROVED	PART NAME:	A公热合式三件套		
.X ±0.30		CHECKED	PART No:	U218-3041-G21077	C	
		DRAWN	PROJECTION:	UNIT:	SCALE:	SHEET:
		DATE	2021.7.23	mm	1:1	10F1
						REV. A